## **SPECIFICATIONS**

Item #902215

## Galaxy® Grow Amp® 600 Watt Select-A-Watt® 400/600/Turbo Charge® Electronic Ballast

c us







This document is not intended to be used for installation purposes. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

	• = yes
•	ETL LISTED
	Tested to UL Standard #1029
LAI	MP COMPATIBILITY
•	HPS - Max. Wattage: 600
•	MH - Max. Wattage: 400
TR	ANSFORMER VOLTAGE
•	120 / 240
	240 ONLY
	277 ONLY
	480 ONLY
AM	PS AT 120V POWER: 5.46
AM	PS AT 240V POWER: 2.73
AM	PS AT 277V POWER: N/A
AM	PS AT 480V POWER: N/A
PO	WER SOURCE Hz: 50/60
PO	WER FACTOR (cosø): > 0.99
AM	BIENT TEMPERATURE: 40°C
TO	TAL HARMONIC DISTORTION: < 10%
PO	WER CORD
•	DETACHABLE 120 VOLT SMART VOLT*
	HARD WIRED 277 VOLT w/ L7-15p TWIST LOCK PLUG
	HARD WIRED 480 VOLT - WIRE ONLY (NO PLUG)
LAI	MP CORD RECEPTACLE COMPATIBILITY
	DUAL UNIVERSAL
•	SUN SYSTEM ONLY
WA	RRANTY
	2 YEAR
•	3 YEAR
	5 YEAR

<sup>\* 240</sup> volt cord sold separately